

3 AA BATTERIES

XPP-5418GX, XPP-5418RX

INTRINSICALLY SAFE FLASHLIGHT

NIGHTSTICK
Life Depends on Light™



Large, textured button that is **easy-to-use with gloves**



Durable polymer body is **impact & chemical resistant**



Non-conductive body for hazardous environments



Sharp focused flashlight beam for **distance illumination**

**ATEX
ZONE 0
IECEX**

**CLASS I
DIV 1**

**IP-67
DUST/WATER
PROOF**

AVAILABLE IN SAFETY RED



200 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

INTRINSICALLY SAFE FLASHLIGHT

3 AA BATTERIES (not included)

ITEM NUMBER/UPC

- XPP-5418GX, UPC 0 17398 80619 0
- XPP-5418RX, UPC 0 17398 80621 3

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, fire and rescue

CERTIFICATIONS

- cETLus, ATEX, IECEX, CE, NFPA, KOSHA, UKCA, InMetro

CASE MATERIAL

- Engineered polymer

FLASHLIGHT LUMENS/RUNTIME

- 200L, 10.5 hrs. runtime

CANDELA

- 5,129

BEAM DISTANCE

- 143 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 5.6 in (142 mm)
- HANDLE DIAMETER: 0.75 in x 1.4 in (19 mm x 35 mm)
- HEAD DIAMETER: 1.5 in (38 mm)
- WEIGHT: 5.4 oz (153 g)

POWER SOURCE








- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight

FL 1 STANDARD		
		
		
<p>  Bayco Products, Inc. 640 S. Sanden Blvd., Wylie, TX 75098 XPP-5418GX Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS CLASS I DIV 1 GRP A D T3 Ex ia op ia IC T3 Ga IECEx IIS 16.0067X CLASS II DIV 1 GRP E-G T130°C Intertek IIS 13 ATEX27837X 1.5V/Cell with three in series CLASS I ZONE 0 AEx ia IC T3 Ga IT321UKEX0264X Emergency ESI or EN51 ID 4003544 22-AV480-0215X UK CA 0359 © 11 1 G Ex ia op ia IC T3 Ga SEE INSTRUCTION MANUAL MFG MM-YY INTRINSICALLY SAFE SECURITE INTRINSEQUE VOIR MANUEL </p>		
<p>CERTIFIED</p> 